



**XPressEntry / Prowatch**  
**Data Manager Synchronization**  
Revision 7/29/2020

For use with the  
XPressEntry Mobile Access Control System

By

◆TELAERIS, Inc.

## Important Notice

Your right to copy XPressEntry software and this manual is limited by copyright laws. Making copies, adaptations, or compilation works (except copies of XPressEntry software for archival purposes as an essential step in the utilization of the program in conjunction with the equipment), without prior written authorization of Telaeris, Inc., is prohibited by law and constitutes a punishable violation of the law.

This software and documentation are copyrighted by Telaeris, Inc. The software and documentation are licensed, not sold, and may be used or copied only in accordance with the Telaeris License Agreement accompanying the software.

© 2020 Telaeris, Inc.

All rights reserved worldwide.

Information in this document is subject to change without notice.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, scanning, digitizing, or otherwise, without the prior written consent of Telaeris, Inc.

## Trademark Acknowledgements

XPressEntry is a trademark of Telaeris, Inc.

Microsoft, Windows, Access are trademarks or registered trademarks of Microsoft Corporation.

Other company and product names may be trademarks or registered trademarks of their respective companies and are hereby acknowledged.

Telaeris, Inc.  
4101 Randolph St  
San Diego, California 92103  
United States of America

(858) 627-9700

[www.telaeris.com](http://www.telaeris.com)

## Table of Contents

|  |           |
|--|-----------|
| <b>Purpose .....</b>   | <b>3</b>  |
| Prerequisites.....   | 3         |
| <b>Setting Up Prowatch to Synchronize with XPressEntry .....</b>         | <b>4</b>  |
| Installing the Pro-Watch API Service .....                               | 4         |
| Configuring the Prowatch API.....  | 4         |
| <b>Prowatch API User Account.....</b>                                    | <b>5</b>  |
| Enabling a Pro-Watch user .....  | 5         |
| User Permissions .....   | 6         |
| <b>Setup Prowatch Readers and Clearance Levels.....</b>                  | <b>8</b>  |
| Clearance Codes.....   | 14        |
| Add Logical Devices to Areas .....                                       | 15        |
| <b>Enable Data Manager Synchronization in XPressEntry .....</b>          | <b>17</b> |
| Determine which Data Manager features you want to use with Prowatch..... | 17        |
| Prowatch Specific Data Manager Options.....                              | 18        |
| <b>Initial Data Synchronization and Setup XPressEntry Data .....</b>     | <b>21</b> |
| <b>Set up Prowatch Areas as XPressEntry Zones .....</b>                  | <b>21</b> |
| Troubleshooting occupancy.....   | 22        |
| <b>Set Up XPressEntry Handheld Readers and Doors.....</b>                | <b>23</b> |
| Doors .....  | 23        |
| Readers .....  | 23        |

## **Purpose**

This document is intended to instruct system administrators on how to synchronize an XPressEntry system with Honeywell Prowatch system.

## **Prerequisites**

It is assumed that you have installed Honeywell Prowatch and XPressEntry in places on a network where they can talk to each other(or on the same box)

Prowatch should be licensed to use the Web API

You should be an Administrator or super user in the Prowatch system.

## Setting Up Prowatch to Synchronize with XPressEntry

It is assumed that Honeywell Prowatch v4.4 or v4.5 is installed on a server.

For integrations into other versions of Prowatch, please contact Telaeris to confirm compatibility.

Prowatch requires that you have their Prowatch API installed. Contact your Honeywell representative for more information on licensing and installation of the Prowatch API.

## Installing the Pro-Watch API Service

(this section is gratuitously copied from the Pro-Watch\_DTU\_Service.pdf file)

1. Create and copy the Pro-Watch API zip file to a folder below the Pro-Watch installation directory
2. If upgrading from a previous version, run the Uninstall\_PW\_DTU\_Service.bat file as administrator to remove the Pro-Watch DTU Service from Windows services. Delete old version.
3. In the DTU Service directory below the Pro-Watch installation directory, unzip all files to the current directory.
4. Edit the file PW-DTU-Service.exe.config file and set the endpoint and binding sections. The DTU Service is defaulted to use HTTP basic binding with no security.
5. Run the Install\_PW\_DTU\_Service.bat file as an administrator. This will add a Windows service called ProWatch DTU Service.
6. In Windows Services, right click on the Pro-Watch DTU Service and select Properties.
7. Select the 'Log On' tab and add a user account to the service that has access to the Pro-Watch server and the Pro-Watch database.

**Note:** The DTU Service account must have access to the Pro-Watch database in SQL Server, be a valid user in Pro-Watch and have Pro-Watch access to that workstation/server. The same account that is used for Pro-Watch can and is suggested to be used for the Pro-Watch DTU service. When using a service account please run the following command to reserve the URL (as specified in API configuration file).

Sample: Netsh http add urlacl url=http://machinename:8734/pwapi user=DOMAIN\accountname

8. In Windows Services, start the Pro-Watch DTU Service.

## Configuring the Prowatch API

For The API Synchronization to work properly, we need to setup two API's in Prowatch. The SOAP and SignalR API.

The following 4 keys need to be set in the PW-DTU-WinService.exe.config file

Note that if you are installing XPressEntry on a different machine than the API, you'll need to change the "localhost" to "your machine name" in these keys.

```
<!-- Start the Pro-Watch SOAP API -->
```

```

<add key="StartSOAPService" value="1" />
<!-- Start the Pro-Watch SignalR API -->
<add key="StartEventService" value="1" />
<!-- Event Service Url -->
<add key="PWEventSignalRUrl" value="http://localhost:8735/" />

<!--Service Configuration -->
<services>
  <service behaviorConfiguration="ProWatchDTUServiceBehavior"
name="HoneywellAccess.ProWatch.PWServiceSoap.PwDtuService">
    <endpoint binding="basicHttpBinding"
bindingConfiguration="ProWatch_DTU_Basic_Http_Binding"
contract="HoneywellAccess.ProWatch.PWServiceSoap.IPwDtuService" name="basicHttpBinding"
bindingNamespace="http://HoneywellAccess/ProWatch/DTUService" />
    <endpoint address="mex" binding="mexHttpBinding" contract="IMetadataExchange" />
  <host>
    <baseAddresses>
      <add baseAddress="http://localhost:8732/ProWatch/DTUService" />
    </baseAddresses>
  </host>
</service>
</services>

```

## Prowatch API User Account

(this section is also gratuitously copied from the Pro-Watch\_DTU\_Service.pdf file)

### Enabling a Pro-Watch user

1. In Pro-Watch, select Database Configuration
2. Select Users or Classes
3. Edit or create a user who will be connecting to the Pro-Watch DTU Service.
4. Select the Programs tab
5. Expand Database Configuration
6. Select 'User Defines'
7. Click the 'Add Function' button
8. Add 'Enable Web Password'
9. Save the User or Class record. Now the 'Web Password' for the User should be enabled.
10. Enter a 'Web Password' and save the User record.

**Edit Users**

**Define User**

User Name:  Class Id:

Last Name:  First Name:

Badge Name:  Id Expiration:  ☒ Never Expires

User PIN Code Settings:

- ☐ Defer to Class
- ☒ No PIN code
- ☐ User PIN code

PIN code:

Status Code:  Supervisor PIN:

Default Package:  ☐ Defer to Class

Eventviewer Pause Time Interval (in min):

Joystick Controllers:

User Pin:  Priority:

**Web Password**:

**Contact Details**

Email:

Cell Phone:


**Two Factor Authentication**

- ☐ Defer to Class
- ☐ Enable
- ☒ Disable

**OK** **Cancel**

## User Permissions

The following minimal Permissions are needed at the API user level in Prowatch:



**Administration -> Data Transfer Utility -> Issue Event** is only needed if we're sending activities to Prowatch

**Administration -> Data Transfer Utility -> Subscribe to Events** is only needed if we're using the SignalR API

These are required because XPressEntry makes the following calls via the API:

- IssueReaderEvent
- GetAreaOccupants
- GetCompanies
- GetBadgeTypes
- GetAreas
- GetLogDevsByHWClass or GetLogicalDevicesAll
- GetClearanceCodes
- GetClearanceCodesLD
- QueryBadgesPaging
- GetBadgeBlob or GetBadgePhoto




## Setup Prowatch Readers and Clearance Levels

If you want to send events into Prowatch, you'll need to setup a Channel/Panel/Readers as placeholders to receive the events from XPressEntry.


For each physical handheld, we should set up two logical device readers (IN/OUT) in Prowatch. If we are just doing Mustering, you only need one logical device per handheld.

You can do that like this:

### Hardware Configuration -> Add a Channel



## Select PW-5000/PW6000



The "Create a Channel" dialog box features a sidebar on the left with a "PRO-WATCH SECURITY MANAGEMENT SYSTEM" logo. The main area is titled "Pick New Channel Type and Options". It contains a "Channel Type" dropdown menu with the selected value "Pw-5000/Pw-6000/Pw-6K1ICE" and a "Manufacturer" text box containing "Northern Computers". At the bottom are "OK" and "Cancel" buttons.

Create a Channel


Pick New Channel Type and Options

Channel Type : Pw-5000/Pw-6000/Pw-6K1ICE

Manufacturer : Northern Computers

OK Cancel

Give it a name, then click Next, Next and then Finish(the options don't matter as we're just using this channel and panels as placeholders for reader events).  
Check "Installed" only initially. Select the TimeZone for now.



The "Define Channel Information" dialog box has a sidebar with the "PRO-WATCH SECURITY MANAGEMENT SYSTEM" logo. The "Basic Channel Information" section includes a "Description" text box with "Sample Channel", an "Installed" checkbox that is checked, a "Channel Type" dropdown with "PW-5000/PW-6000/PW-6K1ICE", a "Time Zone" dropdown with "(GMT-08:00) Pacific Time (US and Canada, Tijuana)", and text boxes for "Attempts" (10), "Poll Delay (ms)" (5), and "Comm Break" (5). At the bottom are "Spool Directory" and "Spool File" text boxes. Navigation buttons at the bottom are "< Back", "Next >", and "Cancel".

Define Channel Information

Basic Channel Information

Description : Sample Channel ☒ Installed

Channel Type : PW-5000/PW-6000/PW-6K1ICE

Time Zone : (GMT-08:00) Pacific Time (US and Canada, Tijuana)

Attempts : 10

Poll Delay (ms) : 5

Comm Break : 5

Spool Directory : Spool File : 0

< Back Next > Cancel

Communications Parameters

Channel Communication Information

Primary  
Port Type: None

Secondary  
Port Type: None

< Back Next > Cancel

PW-5000/6000 Parameters

PW-5000/6000 Encryption Setup

Select Action  
☒ No Encryption  
☐ Use Encryption for Communication

Select Primary Key  
☒ Primary Key 1  
☐ Primary Key 2

Primary Key 1 Settings  
☒ Passphrase  
☐ 128 Bit HEX Key  
Generate Random  
Last Download Status  
Download Key

Primary Key 2 Settings  
☒ Passphrase  
☐ 128 Bit HEX Key  
Generate Random  
Last Download Status  
Download Key

☐ Use 256-bit Encryption  
☒ Use Honeywell Protocol

< Back Next > Cancel

Next we will add a Panel to the Prowatch System.  
Under Hardware Configuration, Right click on Panels and select New -> Panel  
Choose the Site and Channel.

Select a PW-5000 or PW-6000 Controller type.

Pro-Watch Controller Manager

Welcome to the Pro-Watch Controller Manager

|   |  |
|---|--|
| Controller Description                      | Site   |
| <input type="text" value="Sample Panel"/>   | <input type="text" value="NexWatch"/>                  |
| Channel Description                         | Channel Type   |
| <input type="text" value="Sample Channel"/> | <input type="text" value="PW-5000/PW-6000/PW-6K1ICE"/> |
|   | Controller Type  |
|   | <input type="text" value="PW-5000"/>                   |

Controller Address

Hit Next and add a PW5000 2R for each Handheld doing Entry/Exit.

Pro-Watch Controller Manager

Welcome to the Pro-Watch Controller Manager

Please select the downstream boards used and their address

| Downstream Board | Address | Downstream Board | Address |
|------------------|---------|------------------|---------|
| PW5000 2R        | 0       | None             |         |
| PW5000 2R        | 1       | None             |         |
| None             |         | None             |         |
| None             |         | None             |         |

If you need to add additional downstream boards, click the 'More' button, otherwise 'Finish'

More Back Finish Cancel


Then hit Finish.

Now we need to add the Logical Device Readers to the Panel.


Under Hardware Configuration, right click on Readers and select New -> Logical Device

Select the correct Panel we just created

Set the Hardware Template to DoorTypical ACR (Access Control Reader) or Entry/Exit Reader Door.



Then hit Next and Select a port(s) for the reader(s). If you're using the Entry/Exit Reader Door, this will pair the two logical devices for Entry/Exit automatically.



If none exists, go back to the panel and add a reader port.  
Then hit Finish

When you're done, uncheck the Installed checkbox under the Panel.


## Clearance Codes

Add the readers to the appropriate Clearance Codes if we're doing Entry/Exit

To do that, go to Database Configuration -> Clearance Codes.

Either select the appropriate Clearance to add the readers to or add a new one

Note that this isn't needed if we're only doing Mustering.



### Add Logical Devices to Areas

Next you need to make sure your current Prowatch readers and XPressEntry readers are mapped to Areas in Prowatch properly.

This is done from Database Configuration -> Area

Add or Select the areas you want the readers to go In/Out of. Click the Logical Device on the left, then the Reader in the middle. Then use the right arrow to move the device. Click the In/Out X to set whether the device puts the user in/out



Pro-Watch NT Database Configur

- Alarm Pages
- Application Module
- Area
- Badge Profiles
- Badge Status
- Badge Types
- Blob Types
- Brass Keys
- Card Format
- Classes
- Clearance Codes
- Companies
- Database Tables
- Default Events
- Deferred Access
- Dialup Schedules
- Event Procedures
- Event Triggers
- Event Types
- Galaxy User Management
- Groups
- Guard Tours
- Holidays
- Keyboard Accelerator
- Map Files
- Mercury Keypad Settings
- Modem Pools
- Partitions
- Pathway
- Routing Groups
- Status Groups
- Time Zones
- Users
- Workstation

PW Area 2 PW Inside PW Outside

Edit Area

Area Logical Device (Reader) Logical Device (Input) CHIP Reader Mode Area Occupants Partitions

Logical Device

- Area 2 IN
- Area 2 OUT
- IN Only Reader
- In Out Door
- OUT Only Reader
- Sample Handheld IN
- Test Reader/Door Or Whate...
- XPE In
- XPE Out

Reader

- Area 2 IN - Reader

Selected Reader

|                     | In | Out | Internal |
|---------------------|----|-----|----------|
| Area 2 IN - Reader  | X  |     |          |
| Area 2 OUT - Reader |    | X   |          |

Click the device

Click it again (note that for Entry/Exit Door Reader types, you'll have primary/secondary options here)

Click this to add it to the right


Click the In/Out/Internal Columns to set In/Out properly

OK Cancel

## Enable Data Manager Synchronization in XPressEntry

Next is going to be setting up XPressEntry to synchronize the data from Prowatch. This is all managed from within the XPressEntry server application under Tools -> Settings -> Data Manager

At the top, check the Enable Data Manager and then set the Type to Prowatch DTU



## Determine which Data Manager features you want to use with Prowatch

- 1) Send Activities
- 2) Receive Activities
- 3) Occupancy
- 4) Include specific features for the data manager

Here's what the options do:

### **Pull Data Manager Activities into XPressEntry:**

When SignalR is enabled, this adds the events from Prowatch into XPressEntry as badge activities.

### **Push XPressEntry Activities to Data Manager:**

This will use the Channel/Panels/Readers above to send activities into Prowatch.

### **Pull Data Manager Occupancy**

This synchronizes the Area Occupants from Prowatch with XPressEntry.

### **Watch Tables via Software Events**

This enables the SignalR event piece

**Default Role**

The default role to assign to Badges(users) when synchronizing users from Prowatch.

**No Synchronous Syncs**

Used to make sure only one sync(Full,Partial,Occupancy,Activity) is running at any given time. Not necessary for this integration.

**Activity Sync Now**

Runs the Activity Sync process. For Prowatch this will Pull the occupancy AND send activities to the data manager immediately. This is not necessary, but was used in previous versions of the Prowatch Data Manager.

**Occupancy Sync Now**

Synchronizes the area occupants from Prowatch into XPressEntry. Needed for Mustering. It's suggested to set this to every 5 minutes. This will "catch up" any activities that were missed if either service was offline for a significant period of time.

**Partial Sync Now**

This synchronizes all non-user data. This includes Panels/Readers/Clearances/Companies, etc.

**Full Sync Now**

This runs a Partial Sync and also synchronizes user data

**Prowatch Specific Data Manager Options**

Next you should hit the big "Setup Data Manager" button in the top-right. This will take you to the Prowatch Specific Data Manager options.

**Prowatch Data Manager**

**Server**

Server IP:

☐ Use HTTPS

Port:

User:

Password:

**Events**

Event User:

Event Workstation:

Event Types:

☐ Use LOCAL\_GRANT instead of HOST\_GRANT

**Badges Filters**

☐ Only Active Cards    ☐ Only Active Badges

Company Codes Filter:

Clearance Codes User Filter:

Exclude Badge and Card Filter:

Exclude Badge Field:

Last Name Filter (TEST ONLY):

**Other Data Filters**

Area Names Filter:

Readers Names Filter:

Clearance Codes Group Filter:

Reader HW Class ID's:

☒ No Groups Data

☒ Use Prowatch Areas/LogDevs as Doors for Occupancy

**Sync Options**

Page Size:

☐ Disable Picture Updates

Default Area:

**Occupancy Areas**

☒ PW Area 2

☐ PW Inside

☐ PW Outside

**Source Columns    Destination Columns**

| Source Field | XPressEntry Field |
|--------------|-------------------|
| *            |                   |

10:25:26 AM : Connection Success! DTU Service : 1.12.0.746  
PW Version:Release 4.4

The following are required:

The Server IP(and port if you changed it), User and Password

Check the “Use Prowatch Areas/LogDevs as Doors for Occupancy” if you’re doing Mustering or occupancy tracking.

If you’re NOT doing Entry/Exit, check the “No Groups Data” checkbox.

If you want to use SignalR, set the Event User (likely the same as the API user) and the Event Workstation(this is the workstation from Prowatch for the XPressEntry service).

You can map fields from the Prowatch Badge to the XPressEntry User with the Source/Destination Columns on the left(don’t forget to hit the green plus button)

You can select which Prowatch Areas we are actually tracking Occupancy in the bottom right. Note that these will populate only after a Partial Sync has been done. The practical side of this means that you need to come in here, setup everything, then go out and press Partial Sync Now, then come back in here to setup the occupancy Areas.

The remainder of the options are self explanatory but can all be left blank/unchecked if in doubt.

“Test Connect” will tell you whether the API is connected (but not SignalR)

Hit OK when done and then press “Save” on the Data Manager page.

If SignalR is working, you should see something like this:

```
VERBOSE: No Errors in ProwatchDataManager while StartWatchingTables  
INFO: SignalR Event Subscription Started
```

## Initial Data Synchronization and Setup XPressEntry Data

It's suggested to run a Partial Sync first to get the Readers/Clearances/Zones all synchronized and set up.

After you've setup that data in XPressEntry, run a Full Sync.

## Set up Prowatch Areas as XPressEntry Zones

Before doing this, make sure you've done a Partial Sync with the Prowatch system

Prowatch Areas will be mapped to the XPressEntry Zones table.

For each area where you want to track occupancy, you'll need to do the following.

- 1) Make sure that "Zone is Outside" and "Zone is a Muster Point" are unchecked
- 2) Make sure that "Zone is a Hazard Area" is checked

|   |
|---|
| Name  |
| PW Area 2   |
| Description   |
|   |
| Parent Zone   |
|   |
| <input type="checkbox"/> Zone is Outside                  |
| <input type="checkbox"/> Zone is a Muster Point           |
| <input checked="" type="checkbox"/> Zone is a Hazard Area |

For Muster Points, they should be the opposite.

---

Name  
PW Outside

Description

Parent Zone

☒ Zone is Outside  
☒ Zone is a Muster Point  
☐ Zone is a Hazard Area

### Troubleshooting occupancy

If occupants aren't showing up in Zones in XPressEntry, there are some things to check.

- 1) Check that the Channel you're using in Prowatch is added to the Routing Groups for the user
- 2) Make sure you have logical devices assigned to Areas in Prowatch
- 3) In XPressEntry, make sure the zones are setup and selected as above. If all 3 checkboxes are set, the zone won't track occupancy!
- 4) Make sure the Data Manager options for "Pull Data Manager Occupancy" and "Watch Tables via Software Events" are checked.
- 5) Make sure the Doors in XPressEntry are setup properly. (especially if you didn't check the "Use Prowatch Areas/LogDevs as Doors for Occupancy" in the Prowatch Data Manager Setup form.


## Set Up XPressEntry Handheld Readers and Doors

Before doing this, make sure you've done a Partial Sync with the Prowatch system

### Doors

Doors are directly mapped from the Logical Devices and Areas in Prowatch. These are only automatically created if the devices are assigned to an Area in Prowatch. Otherwise you CAN create local Doors and map them on your own.

If we have done everything correctly, we won't have to do much here. Just verify that the doors we have will move people In/Out of areas properly.



The screenshot shows a configuration form for a door. It includes the following fields:

- Door Name:** A text input field containing "Area 2 IN Door".
- Start Zone:** A dropdown menu with "Outside" selected.
- End Zone:** A dropdown menu with "PW Area 2" selected.
- Door RFID Tag #:** An empty text input field.
- External Entry Reader:** A dropdown menu with "Area 2 IN - Reader" selected.
- External Exit Reader:** An empty dropdown menu.

The way to read these is the Start Zone will be where you are coming FROM on an Entry scan on the handheld device and the End Zone will be where you are going TO on an Entry scan. These are reversed for Exit scans.

The External Entry/Exit Reader fields should match the Logical Devices we've setup in Prowatch


### Readers

Readers are directly mapped from logical devices in Prowatch.


If the timezone for the devices and the timezone for the server are different, you'll need to do some additional setup.

First, enable the "Show Reader Timezones" option in Tools -> Settings -> General -> Add/Edit Display





Then, set the Reader Timezone under the Add/Edit Info -> Readers -> Handhelds section for each device in a different timezone.



Lastly, if you are using the devices for Mustering and want the muster activities sent to Prowatch, set the "External Muster Reader" option for each handheld device.

At this point, you should be able to proceed with the standard XPressEntry Reader Profile options to setup your device.