XPIR SERIES READERS

Tablet Readers



XPressEntry is the handheld solution for access control

XPressEntry readers validate permissions and authenticate credentials against the identity info on record in the access control system database on-the-go from anywhere, record entries and exits where door readers are not practical or available maintaining the latest facility occupancy info, challenge credentials within high security areas, quickly muster employees during a real emergency evacuation, and much more.

XPressEntry handheld readers proudly lead the industry with the most access control integrations and lead the industry with the broadest support for badge technologies plus biometrics.





4101 Randolph Street San Diego, CA 92103 - USA PHONE +1 858.627.9700 FAX +1 858.627.9702 www.telaeris.com sales@telaeris.com

XPIR SERIES READER

Rugged Android Tablet - Designed To Read Any RFID Technology!

Performance Characteristics

Processor	ARM (OCTA Core)	
Operating System	Android 14 / GMS	SCANED (13) MISSING (2) THEATTEN TRACK DESIGN DEEPEN DEE
Memory / Storage	8GB RAM + 128GB storage (expandable)	01/01/01/4 1/2/12/33/A
Camera	Front 5.0MP + Rear 13.0MP, autofocus w/ flashlight	Descent Automoti Diversional A Alexand Descent
Battery	10000mAh/3.8V removeable Li-polymer battery	
Power Supply	USB Type-C interface, supports fast charging	HERITAR ISSUE International Daniela Autometiste Internation 19, 2019 Auto
	PE+2.0, maximum power of 18W, maximum 9V/2A	Read 2
Physical Characteris		
Dimensions	274.9mm (H) x 188.7mm (W) x 23.1mm (D)	
Display	10.1-inch IPS screen, 1920×1200 TFT + 10-point capacitive touch screen	ENER MODE
Weight	1140g (including battery)	And Diver
Temperature	Operating Temp: -20 °C to 60 °C	PRESENT BADGE
Llumidity	Storage Temp: -30 °C to 70 °C	BADOL
Humidity I/O	95% Non-Condensing	<i>m</i> ? Q
ηO	USB 2.0 Type-A x 1, USB Type-C x 1, SIM Card x 2, TF Card (3 in 1 card holder), 12PIN Pogo Pin x 1,	
	3.5mm standard earphone jack x 1	
Dust, Waterproof, &	IP65 certified, MIL-STD-810H certified, 1.22m drop	_
Drop		
Network Characteris		
WLAN	802.11 a/b/g/n/ac (2.4G / 5.8G)	The
Bluetooth	BT5.2, Transmission distance: 10m	he he
4G Cellular (Nano-SIM)	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B17/B20/B28A/B28B, WCDMA: B1/B2/B5/B8, GSM: B2/B3/B5/B8, LTE-TDD: B38/B39/B40/B41	EXIT GRANTED Capian Jacob
GNSS	GPS, GLONASS, BeiDou	
RFID Module Suppor		
Low Frequency (LF)	HID, Indala, FarPointe, EM, CasiRusco, Pyramid,	
	Securakey	
High Frequency (HF)	iClass, SEOS, Mifare, DESFire, PIV, CAC, TWIC, Felicia, Legic, Allegion, STid, ISO15693, Gallagher,	· · · · · · · · · · · · · · · · · · ·
	Paxton, FarPointe	
Ultra-High Frequency	EPC GEN2, or ISO 18000-6C	allo and a lot of the
(UHF)		
Mobile Credentials	HID Mobile Access [®] solutions including HID employee badge and Student ID in Apple Wallet,	
	Safetrust, KleverKey, FarPointe	(c. a)
Read Range	HF/LF: 1-3 in. depending on tag	-] . "
	UHF: Up to 30ft depending on tag	· · · · ·
Accessories		
Included	Hand-strap, 5V4A charging adapter	
Optional	Docking charger, battery, fast charging adapter, vehicle mount, vehicle charger, back-strap, quad charging	



4101 Randolph Street San Diego, CA 92103 - USA PHONE +1 858.627.9700 FAX +1 858.627.9702 www.telaeris.com sales@telaeris.com